

S.HLA - NASADKI 1/2" DŁUGIE 6-KĄTNE METRYCZNE




Norme :

NF ISO 2725-1, NF ISO 1711-1, ISO 2725-1, ISO 1711-1, DIN 3124, ASME B107.5


Opis :

- Profil OGV®: większa siła i bezpieczeństwo, ochrona nakrętek.
- Nasadki długie przeznaczone do gniazd lub długich gwintów.
- Wykończenie: chromowane błyszczące.



Referencje :

	A [mm]	d [mm]	d1 [mm]	L [mm]	L1 [mm]	6-kątny [mm]	[g]
S.12HLA	12	21	17,8	77	12	6	105
S.13HLA	13	21,8	19,0	77	12	6	115
S.14HLA	14	21,8	20,3	77	15	6	120
S.15HLA	15	21,8	21,5	77	15	6	125
S.16HLA	16	22,0	22,8	77	15	6	128
S.17HLA	17	23,0	24,0	77	15	6	140
S.18HLA	18	24,0	25,0	77	18	6	160
S.19HLA	19	25,0	26,5	77	18	6	160
S.21HLA	21	27,0	29,0	77	18	6	200
S.22HLA	22	28,0	30,0	77	21	6	215
S.23HLA	23	29,0	31,5	77	21	6	232
S.24HLA	24	30,0	32,8	77	24	6	255
S.26HLA	26	32,0	35,0	77	24	6	280
S.27HLA	27	33,0	36,5	77	27	6	310
S.28HLA	28	34,0	37,8	77	27	6	330
S.29HLA	29	35,0	39,0	77	27	6	355

	A [mm]	d [mm]	d1 [mm]	L [mm]	L1 [mm]	6-kątny [mm]	[g]
S.30HLA	30	36,0	40,0	77	30	6	355
S.32HLA	32	38,0	42,8	77	33	6	408