


Nasadki i akcesoria udarowe 3/4"

■ NK.A - Nasadki udarowe 3/4" 6-kątne metryczne




NF ISO 2725-2, NF ISO 1711-2, ISO 2725-2, ISO 1711-2, DIN 3129, ASME B107.33

- Dla Państwa bezpieczeństwa należy zawsze używać nasadek udarowych z odpowiednimi pierścieniami i kołkami zabezpieczającymi.

№	A [mm]	⌀ [mm]	d [mm]	d1 [mm]	GA	BA	L [mm]	L1 [mm]	ΔΔ [g]
NK.17A	17	6	44	30	GA.37A	BA.38A	52	12	300
NK.18A	18	6	44	32	GA.37A	BA.38A	50	13	310
NK.19A	19	6	44	33	GA.37A	BA.38A	50	14	315
NK.21A	21	6	44	35	GA.37A	BA.38A	50	15	330
NK.22A	22	6	44	37	GA.37A	BA.38A	50	16	345
NK.23A	23	6	44	38	GA.37A	BA.38A	50	16	350
NK.24A	24	6	44	39	GA.37A	BA.38A	50	17	350
NK.26A	26	6	44	42	GA.37A	BA.38A	50	18	480
NK.27A	27	6	44	43	GA.37A	BA.38A	54	23	480
NK.28A	28	6	44	44	GA.37A	BA.38A	54	23	520
NK.29A	29	6	44	45	GA.37A	BA.38A	54	23	520
NK.30A	30	6	44	47	GA.37A	BA.38A	54	23	545
NK.32A	32	6	44	49	GA.37A	BA.38A	56	23	620
NK.33A	33	6	44	51	GA.37A	BA.38A	56	23	650
NK.34A	34	6	44	52	GA.37A	BA.38A	56	23	680
NK.35A	35	6	44	53	GA.37A	BA.38A	56	23	680
NK.36A	36	6	44	54	GA.37A	BA.38A	56	25	705
NK.38A	38	6	44	57	GA.37A	BA.38A	58	26	890
NK.41A	41	6	44	60	GA.37A	BA.38A	58	28	890
NK.42A	42	6	44	62	GA.37A	BA.38A	58	29	925
NK.46A	46	6	44	67	GA.37A	BA.38A	63	32	1055

■ NK.A - Nasadki udarowe 3/4" 6-kątne calowe



ASME B107.2

- Dla Państwa bezpieczeństwa należy zawsze używać nasadek udarowych z odpowiednimi pierścieniami i kołkami zabezpieczającymi.

№	A ["]	⌀ [mm]	d [mm]	d1 [mm]	GA	BA	L [mm]	L1 [mm]	ΔΔ [g]
NK.3/4A	3/4	6	44	33	GA.37A	BA.38A	50	14	315
NK.13/16A	13/16	6	44	35	GA.37A	BA.38A	50	15	330
NK.7/8A	7/8	6	44	37	GA.37A	BA.38A	50	16	345
NK.15/16A	15/16	6	44	39	GA.37A	BA.38A	50	17	350
NK.1"A	1"	6	44	41	GA.37A	BA.38A	50	18	480
NK.1 1/16A	1 1/16	6	44	43	GA.37A	BA.38A	54	23	480
NK.1 1/8A	1 1/8	6	44	44	GA.37A	BA.38A	54	23	520
NK.1 1/4A	1 1/4	6	44	49	GA.37A	BA.38A	56	23	620
NK.1 5/16A	1 5/16	6	44	53	GA.37A	BA.38A	56	23	680
NK.1 7/16A	1 7/16	6	44	55	GA.37A	BA.38A	56	24	515
NK.1 1/2A	1 1/2	6	44	57	GA.37A	BA.38A	58	26	890
NK.1 5/8A	1 5/8	6	44	60	GA.37A	BA.38A	58	28	890