



SYMBOL: **4933451261**

MANUFACTURER: Milwaukee EAN: 4002395170159

M12 SLED-0 - LED spot light, 750 lm, 12 V, without equipment

- Lumens: 400/750
- Max. run time with M12 B4 battery: 8/4/8 h
- Voltage: 12 V
- Beam distance: 650 m
- Metal housing
- Bulb type: LED
- Battery type: Li-ion
- ${f \cdot}$ No. of batteries supplied: 0
- Weight with battery pack: 0.8 kg







521,10 zł (tax excl.)

(640,95 zł (tax incl.))









Product page link > https://im-narzedzia.pl/en/17718-m12-sled-0-led-spot-light-750-lm-12-v-without-equipment.html

DESCRIPTION

- TRUEVIEW™ high definition lighting.
- Up to 35% longer beam distance than competition 650 m intense and highly focused beam of light with 750 Lumens.
 Especially useful for long range identification utility pole/high voltage cable inspection, inspection of long runs of conduit, cast or copper pipe, under ground work, bridge work.
- $\bullet \ \, \text{Metal housing and impact resistant polycarbonate lens with gasketed rubber cap which protects from moisture for harsh jobsite conditions and impact resistant polycarbonate lens with gasketed rubber cap which protects from moisture for harsh jobsite conditions and impact resistant polycarbonate lens with gasketed rubber cap which protects from moisture for harsh jobsite conditions and impact resistant polycarbonate lens with gasketed rubber cap which protects from moisture for harsh jobsite conditions are considered by the protect of the protect$
- · The reflector produces narrow centre beam with wide peripheral beam.
- Ergonomic grip with rubber overmold enhances user comfort and grip during use
- 45° rubber overmold stand for aiming beam upward during prolonged use when the light is equipped with a compact battery pack.
- Up to 8 hours of runtime with an M12™ REDLITHIUM™-ION 4.0 Ah battery pack.
- Dual function trigger allows momentary or lock-on use.
 Battery fuel gauge displays battery status.

- Hand wrist lanyard to keep the light safe and handy.
 Flexible battery system: works with all MILWAUKEE® M12™ batteries.
- · Supplied without battery and charger.

FEATURES

271101120	
Symbol	M12SLED-0
Nazwa	reflektor LED
Waga [kg]	0.80
Stopień ochrony IP	IP 24
Jasność	400/750 lm