



SYMBOL: **4933443500** MANUFACTURER: **Milwaukee** EAN: **4002395003143**



## M18 BPD-0 - Compact percussion drill 18 V, without equipment, 4933443500

- Voltage: 18 V
- No load speed gear 1/2: 0-450/0-1800 rpm
- Max. percussion rate: 0-28800 bpm
- Max. torque: 50 Nm
- Chuck capacity: 13 mm
- Max. drilling wood/ metal/ masonry: 38/13/16 mm
- Wood screws to: 7 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 1.9/2.1 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



729,00 zł **-10%**

**656,10 zł** (tax excl.)

(807,00 zł (tax incl.))

PayU



Product page

link > <https://im-narzedzia.pl/en/17778-m18-bpd-0-compact-percussion-drill-18-v-without-equipment-493344...>

### DESCRIPTION

- Vibration drilling into concrete: 13 m/s<sup>2</sup>
- Vibration drilling into metal: 0.95 m/s<sup>2</sup>
- Vibration screw driving: 0.66 m/s<sup>2</sup>
- Sound power level: 95.7 dB(A)
- Sound pressure level: 84.7 dB(A)
- Compact percussion drill measuring only 198 mm in length, making it ideal for working in confined spaces.
- High performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Full metal gear box delivers maximum performance and long life.
- 13 mm metal chuck for quick bit changes and bit retention.
- 18 stage torque adjustment for maximum flexibility.
- 3 stage mode selector allows the user to switch between rotary, screw drive and percussion modes quickly and easily.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- Supplied without battery and charger.

### FEATURES

Symbol	M18BPD-0
Typ	udarowa
Nm max	50.00
Częstość udaru [ud/min]	0-28800
Ilość akumulatorów	brak
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	38.00
Średnica wiercenia w metalu	13.00
Średnica wiercenia w murze	16.00
Obroty [obr/min]	0-450/0-1800

