



SYMBOL: **4933464135** MANUFACTURER: **Milwaukee** EAN: **4058546220808**



## M12 FPDx-0 - Sub compact percussion drill with removable chuck 12 V, without equipment, 4933464135

- Voltage: 12 V
- No load speed gear 1/2: 0-450/0-1700 rpm
- Max. percussion rate: 0-25500 bpm
- Max. torque: 44 Nm
- Chuck capacity: 13 mm
- Max. drilling wood/ metal/ masonry: 35/13/13 mm
- Wood screws to: 8 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 1.2 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



959,00 zł **-10%**

**863,10 zł** (tax excl.)

(1 061,61 zł (tax incl.))



Product page

link > <https://im-narzedzia.pl/en/17786-m12-fpdx-0-sub-compact-percussion-drill-with-removable-chuck-12-...>

### DESCRIPTION

- High performance compact 6-in-1 percussion drill system for extreme versatility.
- Removable chuck system with 3 different heads for multiples of applications.
- Brushless POWERSTATE™ motor delivers up to 44 Nm of torque.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- 13 mm keyless chuck, full metal right angle 1/4" hex drive head and full metal offset 1/4" hex drive head.
- 1/4" hex drive behind chuck fitting, reduces drill length to 138 mm when required.
- Full metal planetary gearbox transmission for extreme durability.
- LED light for workspace illumination.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#)
- Standard equipment: removable chuck.
- Supplied without battery and charger.

### FEATURES

Symbol	M12FPDX-0
Typ	udarowa
Nm max	44.00
Częstość udaru [ud/min]	0-25500
Ilość akumulatorów	brak
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	35.00
Średnica wiercenia w metalu	13.00
Średnica wiercenia w murze	13.00
Obroty [obr/min]	0-450/0-1700

