



SYMBOL: **4933446790** MANUFACTURER: **Milwaukee** EAN: **4002395005482**



PLH 28 E - 3 kg L-shape SDS-Plus hammer 800 W, in HD Box, 4933446790

- Low vibration 10.6 m/s² due to patented dual anti-vibration* handle.
- 800 watt motor combined with optimised drilling speed results in unsurpassed drilling performance.
- Reliable safety clutch protects machine and user.
- XE version comes with fast changing FIXTEC adaptor and 13 mm keyed chuck.
- 4 m durable rubber cable.

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~2 389,00 zł~~ **-10%**

2 150,10 zł (tax excl.)

(2 644,62 zł (tax incl.))

PayU

Product page

link > <https://im-narzedzia.pl/en/17937-plh-28-e-3-kg-l-shape-sds-plus-hammer-800-w-in-hd-box-4933446790...>

DESCRIPTION

Vibration chiseling/drilling: 6.8/10.6 m/s²

Sound power level: 101.8 dB(A)

Sound pressure level: 90.5 dB(A)

Hardest hitting corded SDS hammer in its class. Tough, durable hammer with excellent drilling performance in concrete from the high torque motor and gears and a 4.1 joule single blow energy

Good balance and easy handling from the compact L-shape design with dual patented AVS (Anti-Vibration-System) and soft grip handle

Roto-stop and variolock for maximum control when doing light chiselling work

*patent pending

FEATURES

| | |
|------------------------------|----------|
| Symbol | PLH28E |
| Waga [kg] | 3.40 |
| Uchwyt | SDS-Plus |
| Częstość uderu [ud/min] | 0-4000 |
| Energia uderu | 4.10 |
| Moc [W] | 800 |
| Zasilanie | network |
| Średnica wiercenia w betonie | 28.00 |
| Średnica wiercenia w drewnie | 40.00 |
| Średnica wiercenia w metalu | 13.00 |
| Obroty [obr/min] | 0-1500 |