



SYMBOL: **4933441947** MANUFACTURER: **Milwaukee** EAN: **4002395002719**



M12 CH-0 - Sub compact SDS-Plus hammer 12 V, FUEL, in HD Box, without equipment, 4933441947

- Voltage: 12 V
- Blow energy: 1.1 J
- Full load hammer action: 0-6575 bpm
- No load speed: 0-900 rpm
- Max. drilling wood/steel/concrete: 13/10/13 mm
- Optimised drilling capacity in concrete: Ø 5.5 - 12 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack (M12 B2): 1.7 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~1 229,00 zł~~ **-10%**

1 106,10 zł (tax excl.)

(1 360,50 zł (tax incl.))

PayU **VISA** MasterCard

Product page

link > <https://im-narzedzia.pl/en/17986-m12-ch-0-sub-compact-sds-plus-hammer-12-v-fuel-in-hd-box-without...>

DESCRIPTION

- Industry's first brushless compact 12V rotary hammer with 1.1 Joules (EPTA), 0 - 6575 bpm & 0 - 900 rpm.
- Exceptionally low vibration value 4.4 m/s² can be used for 8 hours in a day.
- Will drill over 60 50 mm x 6 mm holes per battery charge.
- Superior power to weight ratio in its class with brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more run time.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- 2-mode operation: choose rotary hammer or rotation only for maximum versatility.
- Optimised hammer drilling up to 6 - 10 mm (max 13 mm).
- 43 mm neck size - compatible with M12 DE dust extractor.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.
- Supplied without battery and charger.

FEATURES

Symbol	M12CH-0
Waga [kg]	1.50
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-6575
Energia uderu	1.10
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	12
Średnica wiercenia w betonie	13.00
Średnica wiercenia w drewnie	13.00
Średnica wiercenia w metalu	10.00
Obroty [obr/min]	0-900