



SYMBOL: **4933459733** MANUFACTURER: **Milwaukee** EAN: **4058546029050**



## M18 ONEFHIWF1-802X - 1" Impact wrench, 18 V, 8.0 Ah, ONE-KEY™, in case, with 2 batteries and charger, 4933459733

- Voltage: 18 V
- Max. torque: 530/1020/1800/2033 Nm
- Nut-busting torque: 2400 Nm
- Impact rate: 1350/1650/2100/0-2500 ipm
- No load speed: 0-950/0-1080/0-1370/0-1670 rpm
- Max. bolt diameter: M42
- Tool holder: 1" square
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 8.0 Ah
- Charger supplied
- Weight with battery pack: 5.9 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



4 729,00 zł **-10%**

**4 256,10 zł** (tax excl.)

(5 235,00 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://im-narzedzia.pl/en/20004-m18-onefhiwf1-802x-1-impact-wrench-18-v-80-ah-one-key-in-case-wi...>

### DESCRIPTION

- World's first cordless 18V 1" high torque impact wrench replacing AC, petrol and pneumatic wrenches.
- The M18 FUEL™ high torque impact wrench delivers 2033 Nm of fastening torque at half the size and weight of AC, petrol or pneumatic solutions.
- Delivers up to 2400 Nm of nut-busting torque that enables bolts up to M42 to open.
- The 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting.
- ONE-KEY™ tool control enables wireless tool customisation for increased productivity and consistent results.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- Standard equipment: side handle, metal friction ring.
- Supplied in case (HD Box) with 2 batteries and charger.

### FEATURES

Symbol	M18ONEFHIWF1-802X
Wyjście	1"
Nm max	2033
Częstość uderu [ud/min]	1350/1650/2100/2500
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	950/1080/1370/1670