



SYMBOL: **4933464517** MANUFACTURER: **Milwaukee** EAN: **4058546224622**



M18 BLPD2-502X - Brushless percussion drill 18 V, 5.0 Ah, in case, with 2 batteries and charger, 4933464517

- Voltage: 18 V
- No load speed gear 1/2: 0-550/0-1800 rpm
- Max. percussion rate: 0-28800 bpm
- Max. torque: 82 Nm
- Chuck capacity: 13 mm
- Speed settings: 2
- Max. drilling wood/ metal/ masonry: 76/13/16 mm
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 5.0 Ah
- Charger supplied: 59 min
- Weight with battery pack: 2.1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~2 479,00 zł~~ **-10%**

2 231,10 zł (tax excl.)

(2 744,25 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://im-narzedzia.pl/en/20060-m18-blpd2-502x-brushless-percussion-drill-18-v-50-ah-in-case-wit...>

DESCRIPTION

- New brushless motor design delivers 40 % more torque than previous model - up to 82 Nm.
- Compact design (180 mm in length) provides excellent balance and control, ideal for overhead applications or work in tight spaces.
- Advanced 13 mm heavy duty metal chuck for quick bit changes and superior bit retention.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Optimised speed for faster drilling & fastening (0-550/ 0-1800 rpm).
- On board fuel gauge and LED light.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- Supplied in case (HD Box) with 2 batteries and charger.

FEATURES

Symbol	M18BLPD2-502X
Typ	udarowa
Nm max	82.00
Częstość udaru [ud/min]	0-28800
Ilość akumulatorów	2
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica uchwyty wiertarskiego	13.00
Średnica wiercenia w drewnie	76.00
Średnica wiercenia w metalu	13.00
Średnica wiercenia w murze	16.00
Obroty [obr/min]	0-550/0-1800

