



SYMBOL: **4933464527** MANUFACTURER: **Milwaukee** EAN: **4058546224721**



## M18 ONEPD2-502X - Percussion drill 18 V, 5.0 Ah, ONE-KEY™, in case, with 2 batteries and charger, 4933464527

- Voltage: 18 V
- No load speed gear 1/2: 0-550/0-2000 rpm
- Max. percussion rate: 0-32000 bpm
- Max. torque: 135 Nm
- Chuck capacity: 13 mm
- Speed settings: 2
- Max. drilling wood/ metal/ masonry: 89/16/16 mm
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 5.0 Ah
- Charger supplied: 59 min
- Weight with battery pack: 2.2 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~2 909,00 zł~~ **-10%**

**2 618,10 zł** (tax excl.)

(3 220,26 zł (tax incl.))

PayU VISA MasterCard



Product page

link > <https://im-narzedzia.pl/en/20066-m18-onepd2-502x-percussion-drill-18-v-50-ah-one-key-in-case-with...>

### DESCRIPTION

- Higher power efficiency under load - outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
- Connect via Bluetooth® with the ONE-KEY™ app.
- Customise anti-kickback control via ONE-KEY™ app.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite.
- Configure to any application choosing optimum tool settings for repeatable precision.
- Control speed, torque, start and end speeds, anti-kickback functions and LED.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- **Supplied in case (HD Box) with 2 batteries and charger.**

### FEATURES

Symbol	M18ONEPD2-502X
Typ	ударова
Nm max	135.00
Częstość uderu [ud/min]	0-32000
Ilość akumulatorów	2
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	89.00
Średnica wiercenia w metalu	16.00
Średnica wiercenia w murze	16.00
Obroty [obr/min]	0-550/0-2000