



SYMBOL: 4933451792

MANUFACTURER: Milwaukee EAN: 4002395277650

M18 FQID-0 - 1/4" HEX impact driver 18 V, FUEL™ SURGE, without equipment, 4933451792

- · Voltage: 18 V
- Impact rate: 1800/2900/4000/4000 ipm
- No load speed: 900/2100/3000/3000 rpm
- Max. torque: 50 Nm
- Max. bolt diameter: M14
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 1.7 kg

■ WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



1 479,00 zł -10%

1 331,10 zł (tax excl.)

(1 637,25 zł (tax incl.))



Pay**U** VISA MasterCard









link > https://im-narzedzia.pl/en/20103-m18-fqid-0-14-hex-impact-driver-18-v-fuel-surge-without-equipmen...

DESCRIPTION

- Sound pressure level: 87.9 dB(A)
- Sound power level measured: 98.9 dB(A)
 The M18 FUEL™ SURGE™ 1/4* Hex hydraulic driver is Milwaukee Tool's quietest impact driver
- FLUID-DRIVE™ hydraulic powertrain reduces metal on metal contact within the tool, delivering quieter operation, smoother performance and increased durability over a standard impact.
- · Delivers same performance in wood fastening as standard brushless impact drivers.
- POWERSTATE™ brushless motor delivers up to 0 3.000 rpm with constant power output to drive screws faster
- REDLINK PLUS™ intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Self-tapping screw mode is designed to reduce walking when starting self-tapping screws as well as reduce overdriving, breaking and stripping out screws.

 REDLITHIUM**-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- $\cdot \text{Individual battery cell monitoring optimises tool run time and ensures long term pack durability} \\$
- •1/4" Hex chuck for quick and easy bit change.
- On board fuel gauge and LED light.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- · Supplied without battery and charger.

FEATURES

27.1.01.120	
Symbol	M18FQID-0
Wyjście	1/4"
Nm max	50
Częstość udaru [ud/min]	1800/2900/4000/4000
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	900/2100/3000/3000