



SYMBOL: **4933459724** MANUFACTURER: **Milwaukee** EAN: **4058546028961**



M18 ONEFHIWP12-0X - 1/2" Impact wrench, 1017 Nm, 18 V, ONE-KEY™, in case, without equipment, 4933459724

- Voltage: 18 V
- Max. torque: 190/400/1017/1017 Nm
- Nut-busting torque: 1491 Nm
- Impact rate: 0-1150/0-2100/0-2400/0-2400 ipm
- No load speed: 0-950/0-1500/0-1800/0-1800 rpm
- Max. bolt diameter: M24
- Tool holder: 1/2" square
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 3.2 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~2 169,00 zł~~ **-10%**

1 952,10 zł (tax excl.)

(2 401,08 zł (tax incl.))

PayU

Product page

link > <https://im-narzedzia.pl/en/20134-m18-onefhiwp12-0x-12-impact-wrench-1017-nm-18-v-one-key-in-case-...>

DESCRIPTION

- Sound power level measured: 105,7 dB(A)
- Sound pressure level: 94,7 dB(A)
- The M18 FUEL™ high torque impact wrench with ONE-KEY™ technology delivers 1017 Nm of fastening torque in a compact size of 206 mm, which gives more access in tight spaces.
- The 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 4 bolt removal, provides a maximum nut-busting torque of 1491 Nm then shifts to 750 rpm for outstanding control when removing fasteners.
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting.
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- 1/2" pin detent for maximum socket retention.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#)
- **Supplied in case (HD Box) without battery and charger.**

FEATURES

Symbol	M18ONEFHIWP12-0X
Wyjście	1/2"
Nm max	1017
Częstość uderu [ud/min]	1150/2100/2400/2400
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	950/1500/1800/1800

