



SYMBOL: **4933464616** MANUFACTURER: **Milwaukee** EAN: **4058546225612**



**M12 FIWF12-422X - Sub compact 1/2" impact wrench, 339 Nm, 12V, 2.0 and 4.0 Ah, in case, with 2 batteries and charger, 4933464616**

- Voltage: 12 V
- Max. torque: 339 Nm
- Impact rate: 1100/2100/3200 ipm
- No load speed: 1200/1800/2700/2700 rpm
- Max. bolt diameter: M16
- Tool holder: 1/2" square
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 2.0 and 4.0 Ah
- Charger supplied: 80 min
- Weight with battery pack: 1.1 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~1 669,00 zł~~ **-10%**

**1 502,10 zł** (tax excl.)

(1 847,58 zł (tax incl.))

PayU<sup>3</sup> VISA MasterCard

Product page

link > <https://im-narzedzia.pl/en/20149-m12-fiwf12-422x-sub-compact-12-impact-wrench-339-nm-12v-20-and-4...>

## DESCRIPTION

- More power, more compact, more control.
- Up to 339 Nm of maximum torque.
- 1/2" anvil with friction ring for quick and easy socket changes.
- Brushless POWERSTATE™ motor delivers more power in a more compact size.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Better access in tight spaces with an overall length of only 124.5 mm.
- 4-Mode DRIVE CONTROL with auto-shut off mode, offers the user precise control.
- Bright LED workspace illumination.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#)
- Supplied in case (HD Box) with 2 batteries and charger.

## FEATURES

Symbol	M12FIWF12-422X
Wyjście	1/2"
Nm max	339
Częstość uderu [ud/min]	1100/2100/3200
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Obroty [obr/min]	1200/1800/2700/2700