



SYMBOL: **4933464404** MANUFACTURER: **Milwaukee** EAN: **4058546223496**



M12 BPRT-0 - Sub compact rivet tool 12 V, without equipment, 4933464404

- Voltage: 12 V
- Stroke length: 20.32 mm
- Rivet diameter range: 2.4 - 4.8 mm
- Max. pulling force: 9000 N
- Battery type: Li-ion
- No. of batteries supplied: 0
- Dimensions: 273 x 66 x 8 x 230 mm
- Weight with battery pack: 2.1 kg

 **WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



1 639,00 zł **-10%**

1 475,10 zł (tax excl.)

(1 814,37 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://im-narzedzia.pl/en/20170-m12-bprt-0-sub-compact-rivet-tool-12-v-without-equipment-4933464...>

DESCRIPTION

- Sound power and pressure level: 64.1 / 53.1 dB(A)
- Up to 325 x 4.8 mm stainless steel rivets on a single charge with a 2.0 Ah battery pack.
- Suitable for all aluminium, steel, stainless steel and copper rivets up to 4.8 mm.
- Rivets in one stroke with a 20.32 mm stroke length.
- Retention nose pieces hold rivets in any orientation.
- Tool-free access to easily clean jaws. On-board nose piece storage and removal tool for user convenience.
- On board fuel gauge and LED light for added user convenience and illumination in low lit working conditions.
- Ergonomic design with 273 mm H x 66.8 mm W x 165 mm in length without mandrel collector.
- Integrated belt hook and lanyard tie off point.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#).
- Supplied with 4 x retaining tips.
- **Supplied without battery and charger.**

FEATURES

Symbol	M12BPRT-0
Opis	średnica nitów: 2,4 - 4,8 mm
Długość skoku	20.32
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	12

