



SYMBOL: **4933441225** MANUFACTURER: **Milwaukee** EAN: **4002395001262**



M12 BPP3A-202B - POWERPACK M12™, M12 BDD, M12 BID, M12 TLED, 2 x 2.0 Ah + charger, in bag, 4933441225

- Set contains:
 - M12 BDD - sub compact drill driver 12 V
 - M12 BID - sub compact 1/4" HEX impact driver 12 V
 - M12 TLED - LED torch
 - M12 B2 - 2 batteries 2.0 Ah
 - C12 C - charger
- Supplied in a bag.



~~1 589,00 zł~~ **-10%**

1 430,10 zł (tax excl.)

(1 759,02 zł (tax incl.))

PayU VISA MasterCard



Product page

link > <https://im-narzedzia.pl/en/20544-m12-bpp3a-202b-powerpack-m12-m12-bdd-m12-bid-m12-tled-2-x-20-ah...>

DESCRIPTION

M12 BDD

- Voltage: 12 V
- Chuck capacity: 10 mm
- Max. drilling steel/wood: 10/22 mm
- No load speed gear 1/2: 0-400/0-1500 rpm
- Max. torque: 38 Nm
- Wood screws to: 6 mm
- Battery type: Li-ion
- Weight with battery pack (M12 B2): 1.4 kg

- High performance sub compact drill driver measures 189 mm in length making it ideal for working within confined spaces.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- 10 mm metal chuck for quick bit changes and bit retention.
- Optimised handle for better control and improved grip.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

M12 BID

- Voltage: 12 V
- Impact rate: 0 - 3300 ipm
- Max. torque: 112 Nm
- No load speed: 0 - 2500 rpm
- Tool reception: 1/4" Hex
- Battery type: Li-ion
- Weight with battery pack (M12 B2): 1 kg

- High performance sub compact impact driver measures 165 mm in length making it ideal for working within confined spaces.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Heavy duty full metal gearbox and gears for superior durability and maximum torque.
- 1/4" Hex chuck for quick and easy bit change.
- Optimised handle for better control and improved grip.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

M12 TLED

- Voltage: 12 V
- Max. lumens: 120
- System: M12™
- Battery type: Li-ion
- Weight with battery pack (M12 B2): 0.5 kg

- The 120 lumen LED light is 2x brighter and whiter than conventional incandescent bulbs.
- M12™ LED electronics deliver 2x longer run time on a single charge with less heat.
- Sealed aluminium head is designed for impact- and weather-resistant durability.
- 90° rotating head allows the user to easily direct the light beam at the desired work area.
- Magnetic back for hands-free use.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

• Supplied in bag with 2 batteries and charger.

FEATURES

Symbol	M12BPP3A-202B
Opis	wiertarko-wkrętarz, zakrętarz udarowy, latarka, 2 akumulatory, ładowarka
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Pojemność akumulatora [Ah]	2.0

