



SYMBOL: **4933464268** MANUFACTURER: **Milwaukee** EAN: **4058546222130**



M18 FPP2A2-502X - POWERPACK M18™ FUEL™, M18 FPD2, M18 FID2, 2 x 5.0 Ah + charger, in case, 4933464268

- Set contains:
 - M18 FPD2 - percussion drill 18 V
 - M18 FID2 - 1/4" HEX impact driver 18 V
 - [M18 B5](#) - 2 batteries 5.0 Ah
 - [M12-18 FC](#) - charger 59 min
- Supplied in case (HD Box)

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page

link > <https://im-narzedzia.pl/en/20552-m18-fpp2a2-502x-powerpack-m18-fuel-m18-fpd2-m18-fid2-2-x-50-ah-c...>



DESCRIPTION

M18 FPD2

- Voltage: 18 V
- Max. drilling masonry: 16 mm
- Max. drilling steel: 16 mm
- Max. drilling wood: 89 mm
- Max. percussion rate: 0 - 32000 bpm
- Max. torque: 135 Nm
- No load speed gear 1: 0 - 550 rpm
- No load speed gear 2: 0 - 2000 rpm
- Speed settings: 2
- Chuck capacity: 13 mm
- Weight with battery pack (M18 B5): 2.2 kg

- Higher power efficiency under load - outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
- Brushless POWERSTATE™ motor for heavy application under load.
- 13 mm metal chuck for quick bit changes and bit retention.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Battery fuel gauge displays remaining charge.
- 40 percent brighter LED workspace illumination - vs previous model.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FID2

- Voltage: 18 V
- Max. fastening torque: 226 Nm
- Impact rate: 1200/3400/4300/0-4300 ipm
- Max. torque: 119/176/226/0-226 Nm
- Max. bolt diameter: M16
- Tool reception: 1/4" Hex
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 1.7 kg

- Higher power efficiency under load - outstanding torque of 226 Nm.
- Faster driving speed vs. previous model - up to 3600 rpm and 4300 ipm.
- Extremely compact design - total length of just 117 mm for access into tight spaces.
- DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 1 for precision work.
- Mode 2 helps prevent damage to fasteners and material.
- Mode 3 delivers maximum performance for the toughest applications.
- Mode 4 is the optimum between precision work and maximum performance and automatically adjusts speed, impacts and torque.
- Brushless POWERSTATE™ motor for heavy application under load.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- 1/4" Hex chuck for quick and easy bit change.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

- Supplied in case (HD Box) with 2 batteries and charger.



FEATURES

Symbol	M18FPP2A2-502X
Opis	wiertarko-wkrętarka udarowa, zakrętarka udarowa, 2 akumulatory, ładowarka
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.0

