



SYMBOL: **4933464970** MANUFACTURER: **Milwaukee** EAN: **4058546229153**



M12 ONEFTR12-201C - 1/2" Digital torque wrench +/-2%, 12 V, 2.0 Ah, FUEL™, ONE-KEY™, in case with battery and charger, 4933464970

- Voltage: 12 V
- Accuracy: CW ±2%, CCW ±3%
- Torque range: 16.9 - 203.4 Nm
- No load speed: 0-100 rpm
- Tool holder: 1/2" square
- Battery type: Li-ion
- No. of batteries supplied: 1
- Battery pack capacity: 2.0 Ah
- Charger supplied: 40 min
- Length: 596.9 mm
- Weight with battery pack: 2.6 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~4 439,00 zł~~ **-10%**

3 995,10 zł (tax excl.)

(4 913,97 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://im-narzedzia.pl/en/20573-m12-oneftr12-201c-12-digital-torque-wrench-2-12-v-20-ah-fuelone-...>

DESCRIPTION

- Milwaukee Tool's first digital torque wrench, delivers up to 50% faster installation by replacing the hand tool.
- Provides 16.9 - 203.4 Nm of torque range and accuracy within ±2% for torque critical fasteners.
- Faster, more productive torque reporting with ONE-KEY™, providing torque data and customisable reports for inspectors or owners.
- Adjustable run-down torque to control the tools output torque via the motor to prevent over torque.
- Four measurement modes (ft-lb, in-lb, Nm, Kg-cm) and 15 available presets.
- Durable design to withstand the most demanding jobsite environments.
- Four notification modes that the tool is reaching, meeting or exceeding the torque target (audible, LED, LCD, and vibratory).
- Six pre-programmed languages including English, Spanish and French.
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™-ION battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#)
- Supplied in case (Kitbox) with battery and charger.

FEATURES

Symbol	M12ONEFTR12-201C
L [mm]	596.90
Waga [kg]	2.60
Typ	ONE-KEY
Nm min	16.90
Nm max	203.40
Dokładność	±2%
Ilość akumulatorów	1
Zasilanie	battery
Napięcie akumulatora [V]	12