




SYMBOL: 4933471404

MANUFACTURER: Milwaukee EAN: 4058546290320

M18 FFN-502C - Framing nailer 18 V, 5.0 Ah, FUEL™, in case, with 2 batteries and charger, 4933471404

- · Voltage: 18 V
- · Magazine angle: 30/34°
- · Magazine capacity: 57
- · Nail diameter: 2.9/3.32 mm
- Nail type: 50/90 mm
- · Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 5.0 Ah
- Charger supplied: 59 min
- Weight with battery pack: 5.1 kg







4 085,10 zł (tax excl.)

(5 024,67 zł (tax incl.))



Pav**U** VISA MasterCard

Product page link > https://im-narzedzia.pl/en/20577-m18-ffn-502c-framing-nailer-18-v-50-ah-fuel-in-case-with-2-batte...









DESCRIPTION

- Best-in-class power to consistently seat nails sub-flush to the surface in hardwoods
- Ready to Fire Nail Technology eliminates ramp-up time between each nail discharge.
 No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance
- Two mode selection allows for sequential fire for precision or bump fire for speed.
 Tool-free, quick and easy depth adjustment to assure nails are driven sub-flush.
- Dry-Fire lockout stops the tool being fired when there are no nails left in the magazine.
 Fires up to 700 nails per charge on a REDLITHIUM™-ION 5.0 Ah battery pack for maximum productivity.
- Fires standard framing nails which fits an angled magazine at 30° or 34°.
- Quick access and easy clearing of jams.
 LED work light illuminates the work surface for better placement of nails.
- Integrates three MILWAUKEE®-exclusive technologies the POWERSTATE™ brushless motor, REDLITHIUM™-ION battery pack and REDLINK PLUS™ intelligence hardware and software which deliver outstanding power, run time and durability on the jobsite.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- · Supplied in case (Kitbox) with 2 batteries and charger.

-EATURES	
Symbol	M18FFN-502C
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność magazynka	57.00
Średnica gwoździa	2.9/3.32