



SYMBOL: **4933478405** MANUFACTURER: **Milwaukee** EAN: **4058546345969**



M18 ONEFHIWF12E-0X - 1/2" Impact wrench, 1017 Nm, 18 V, ONE-KEY™, in case, without equipment, 4933478405

- Voltage: 18 V
- Max. torque: 102/ 203/ 610/ 1017 Nm
- No load speed: 0-1200/0-1800/0-1800/0-1800 rpm
- Impact rate: 0-1600/0-2400/0-2400/0-2400 ipm
- Nut-busting torque: 1500 Nm
- Max. bolt diameter: M33
- Tool reception: 1/2" square
- No. of batteries supplied: 0
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 3.3 kg



~~2 169,00 zł~~ **-10%**

1 952,10 zł (tax excl.)

(2 401,08 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://im-narzedzia.pl/en/21956-m18-onefhiwf12e-0x-12-impact-wrench-1017-nm-18-v-one-key-in-case-...>

DESCRIPTION

- Max. bolt diameter: M33.
- Weight with battery pack: 3.3 kg.
- The M18 FUEL™ extended anvil high torque impact wrench with ONE - KEY™ technology delivering 1017 Nm of fastening torque with a 75 mm extended 1/2" anvil friction ring reception.
- The 4 -Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- The M18 FUEL™ extended anvil high torque impact wrench with ONE - KEY™ technology delivers 1500 Nm of nut busting torque.
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting.
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Supplied in case (HD Box) without battery and charger.

FEATURES

Symbol	M18ONEFHIWF12E-0X
Wyjście	1/2"
Nm max	1017
Częstość uderu [ud/min]	1600/2400/2400/2400
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	1200/1800/1800/1800