



SYMBOL: **4933472239** MANUFACTURER: **Milwaukee** EAN: **4058546326357**



## M12 FMT-422X - FUEL™ Multi-tool 12 V, 2.0 & 4.0 Ah, in case, with 2 batteries and charger, 4933472239

- Voltage: 12 V
- No load speed: 10000 - 20000 rpm
- Oscillation angle left/right: 1.8°
- Vibration cutting wood: 10.01 m/s<sup>2</sup>
- Vibration cutting wood uncertainty: 1.5 m/s<sup>2</sup>
- Battery type: Li-ion
- Weight with battery pack: 1.6 kg



~~1 869,00 zł~~ **-20%**

**1 495,20 zł** (tax excl.)

(1 839,10 zł (tax incl.))



Product page

link > <https://im-narzedzia.pl/en/21958-m12-fmt-422x-fuel-multi-tool-12-v-20-40-ah-in-case-with-2-batter...>

### DESCRIPTION

- Brushless POWERSTATE™ motor delivers fast cutting speed through common materials without slowing or bogging down in hardwoods.
- Adjustable 10,000 to 20,000 opm allow the user to get the perfect cut whatever the material.
- Lowest vibration in its class, 4.56 m/s<sup>2</sup> driving productivity through performance and safety.
- 1.8° left/right oscillation angle allowing faster cuts.
- Ability to make up to 59 cuts in oak on one 2.0 Ah battery charge.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- FIXTEC™ tool free blade change with universal blade change adaptor included to accept all major competitor blades.
- LED work light illuminates the cut line in low light conditions.
- Supplied with an adapter, plunge cut blade OSC 112, sanding backing pad, 5 x sanding sheets and a DEK26 dust guard to use when sanding.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.
- Standard equipment: Hex wrench, 1 x adapter, 1 x plunge cut blade OSC 112, 1 x sanding backing pad, 3 x grit 60, 3 x grit 80, 3 x grit 120, 3 x grit 240, dust guard, depth stop.
- **Supplied in case (HD Box) with 2 batteries and charger.**

### FEATURES

Symbol	M12FMT-422X
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Obroty [obr/min]	10000-20000