



SYMBOL: **4933478500** MANUFACTURER: **Milwaukee** EAN: **4058546346935**



## M18 FH-0X - 4-mode 26 mm SDS-Plus hammer 18 V, FUEL™, in case, without equipment, 4933478500

- Voltage: 18 V
- Blow energy: 2.5 J
- Max. percussion rate: 0-4800 bpm
- No load speed: 0-1330 rpm
- Max. drilling wood/steel/concrete: 28/13/26 mm
- Vibration drilling: 12.9 m/s<sup>2</sup>
- Vibration chiseling: 14.2 m/s<sup>2</sup>
- Battery type: Li-ion
- Weight with battery pack (M18 HB5.5): 4.3 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~1 959,00 zł~~ **-10%**

**1 763,10 zł** (tax excl.)

(2 168,61 zł (tax incl.))

PayU

Product page

link > <https://im-narzedzia.pl/en/22090-m18-fh-0x-4-mode-26-mm-sds-plus-hammer-18-v-fuel-in-case-without...>

### DESCRIPTION

- The fastest drilling rotary hammer in its class leading to increased productivity.
- Powerful hammer mechanism delivers 2.5 J of impact energy at low 12.9 m/s<sup>2</sup> vibrations.
- Drills up to 125 Ø10 x 50 mm holes on a M18™ HIGH OUTPUT™ 5.5 Ah battery charge.
- AUTOSTOP™ shuts down the tool to protect the user of sharp movement in bind up situations.
- All metal gear case - optimum seating of the gears for enhanced tool life.
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility.
- Compatible with M18 FCDDEXL or M18 FDDEXL dust extractors.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time.
- These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries.
- **Supplied in case (HD Box) without battery and charger.**

### FEATURES

Symbol	M18FH-0X
Waga [kg]	4.30
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-4800
Energia uderu	2.50
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	26.00
Średnica wiercenia w drewnie	28.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1330