



SYMBOL: **4933478506** MANUFACTURER: **Milwaukee** EAN: **4058546346997**



M18 ONEFHXDEL-552C - 4-mode 26 mm SDS-Plus hammer ONE-KEY™ and with dedicated dust extractor 18 V, 5.5 Ah, FUEL™, in case

- Set includes:
- M18 ONEFHX - M18 FUEL™ 4-mode 26 mm SDS-Plus hammer with FIXTEC™ chuck and ONE-KEY™.
- M18 FDDEXL - Dedicated dust extraction for M18 FUEL™ 26 mm SDSPlus hammers with AUTOPULSE™.
- M18 HB5.5 - 2 x 5.5 Ah
- M12-18 FC - charger
- Supplied in case (Kitbox).

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~4 539,00 zł~~ **-10%**

4 085,10 zł (tax excl.)

(5 024,67 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://im-narzedzia.pl/en/22093-m18-onefhxdel-552c-4-mode-26-mm-sds-plus-hammer-one-key-and-with...>

DESCRIPTION

M18 ONEFHX:

- Voltage: 18 V
- Blow energy: 2.5 J
- Max. percussion rate: 0-4800 bpm
- No load speed: 0-1330 rpm
- Max. drilling wood/steel/concrete: 28/13/26 mm
- Vibration drilling: 12.9 m/s²
- Vibration chiseling: 14.2 m/s²
- Tool reception: SDS-Plus + Reduced shank 13 mm
- Battery type: Li-ion
- Weight with battery pack (M18 HB5.5): 4.5 kg
- The fastest drilling rotary hammer in its class leading to increased productivity.
- Powerful hammer mechanism delivers 2.5 J of impact energy at low 12.9 m/s² vibrations.
- Drills up to 125 Ø10 x 50 mm holes on a M18™ HIGH OUTPUT™ 5.5 Ah battery charge.
- AUTOSTOP™ shuts down the tool to protect the user of sharp movement in bind up situations.
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools.
- ONE-KEY™ also features a remote locking functionality.
- FIXTEC™ system for keyless chuck changing between SDS-Plus and 13 mm metal chuck.
- All metal gear case - optimum seating of the gears for enhanced tool life.
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility.
- Compatible with M18 FCDDEXL or M18 FDDEXL dust extractors.

M18 FDDEXL:

- Voltage: 18 V
- Max. drill bit diameter: 26 mm
- Max. drilling depth: 152 mm
- Max. drill bit length: 210 mm
- Stroke length: 152 mm
- Battery type: Li-ion
- Weight: 1.9 kg
- Designed to collect dust efficiently with automatic operation from the tools on/ off trigger switch.
- AUTOPULSE™ industry's first on-board automatic filter cleaning mechanism for an on-tool dust extractor, which increases the air flow efficiency as well as the filter life time.
- The highly efficient HEPA filter collects 99.97 % of airborne particles down to 0.3 microns.
- Translucent dust box allows user to see the current level of dust inside as well as when the dust box is full.
- Dust box with vacuum port allows user to attach to large dust extractors to suction out dust from the box.
- Optimised to be used with AS 30 LAC 30 I dust extractor and DEK26 hose clip adapter (4931447295).
- Exchangeable nozzles to adjust to the different drilling diameters.
- Supplied with 2 nozzle sizes 1x up to Ø16 mm, 1x up to Ø26 mm, which can be quickly switched thanks to the quick lock mechanism.
- Dust extraction aluminium tube is adjustable according to the size of the drill bit and length up to 210 mm depth.
- Adjustable depth gauge with easily and precisely adjustment buttons for accurate hole depths.
- Removable and switchable depth gauge, in case the user prefers the other side.

- Supplied in case (Kitbox) with 2 batteries and charger.

FEATURES

Symbol	M18ONEFHXDEL-552C
--------	-------------------



Waga [kg]	4.50
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-4800
Energia uderu	2.50
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	26.00
Średnica wiercenia w drewnie	28.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1330

