



SYMBOL: **4933478453** MANUFACTURER: **Milwaukee** EAN: **4058546346447**



**M18 FMTIW2P12-502X - 1/2" Mid-torque impact wrench 745 Nm, 18V, 5.0Ah, FUEL™, in case with 2 batteries and charger, 4933478453**

- Voltage: 18 V
- Max. torque: 475/610/745/47 Nm
- Impact rate: 0-900/0-2100/0-3100 ipm
- No load speed: 0-1250/0-1950/0-2575/0-1325 rpm
- Nut-busting torque: 881 Nm
- Max. bolt diameter: M22
- Tool reception: 1/2" square



~~3 199,00 zł~~ **-10%**

**2 879,10 zł** (tax excl.)

(3 541,29 zł (tax incl.))



Product page

link > <https://im-narzedzia.pl/en/22118-m18-fmtiw2p12-502x-12-mid-torque-impact-wrench-745-nm-18v-50ah-f...>

#### DESCRIPTION

- Battery pack capacity: 5.0 Ah
- No. of batteries supplied: 2
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2.3 kg

- Most versatile cordless impact wrench in the MILWAUKEE® impressive arsenal with an industry-leading performance at 881 Nm of nut-busting torque and 745 Nm of fastening torque.
- Incredibly compact design for this performance level, with only 152 mm overall length ideal for applications in tight spaces.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops.
- Auto shut-off control applies no more than 47 Nm of torque for hand-tight fastening applications to prevent over-tightening.
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- 1/2" square detent pin.
- Reversible belt hook.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- **Supplied in case (HD Box) with 2 batteries and charger.**

#### FEATURES

Symbol	M18FMTIW2P12-502X
Wyjście	1/2"
Nm max	745
Częstość uderu [ud/min]	900/2100/3100
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	1250/1950/2575/1325