



## DESCRIPTION

- With up to 47 Nm of max torque and 450 rpm's, this tool delivers faster application speed and increased productivity for the professional user
- 19 mm low profile head design allows users better access in tight spaces.
  Variable speed metal trigger provides ultimate control of the tool.
  The industry leading FUEL<sup>®</sup> technology combined with a reinforced mechanism for greater durability.
- · Rubber overmold withstands most corrosive materials and provides increased comfort.
- The LED light illuminates the work area while the on-board fuel gauge displays remaining run time.
- Fastening and removing of 210 M8 bolts with one battery charge M12B2 for all day work.
  REDLINK PLUS<sup>™</sup> intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM<sup>™</sup> battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
  Flexible battery system: works with all MILWAUKEE® M12<sup>™</sup> batteries.
- · Supplied without battery and charger.

## FEATURES

Symbol	M12FHIR38-0
Wyjście	3/8"
Nm max	47
llość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	12
Obroty [obr/min]	0-450