



SYMBOL: **4933478293** MANUFACTURER: **Milwaukee** EAN: **4058546344702**



## M18 FSZ-0X - Reciprocating saw 18 V, HACKZALL™, FUEL™, in case, without equipment

- Voltage: 18 V
- No load stroke rate: 0-3000 spm
- Max. cutting depth in aluminium/metal pipe/non-ferrous metal/soft-wood/steel: 25/150/25/300/20 mm
- Vibration cutting boards: 26.7 m/s<sup>2</sup>
- Vibration cutting boards uncertainty: 1.5 m/s<sup>2</sup>
- Vibration cutting wooden beam: 25.1 m/s<sup>2</sup>
- Vibration cutting wooden beam uncertainty: 1.5 m/s<sup>2</sup>

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~1 889,00 zł~~ **-25%**

**1 416,75 zł** (tax excl.)

(1 742,60 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://im-narzedzia.pl/en/22147-m18-fsz-0x-reciprocating-saw-18-v-hackzall-fuel-in-case-without-...>

### DESCRIPTION

- Stroke length: 32 mm
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 3.8 kg
- Brushless POWERSTATE™ motor for up to 5x longer motor life and up to 30% faster cutting.
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups.
- Wear resistant lever actuated FIXTEC™ blade clamp provides fast and easy blade changes.
- Metal reinforced battery connection provides improved durability and battery retention over life.
- Built-in LED light illuminates the work surface while cutting.
- Adjustable shoe for optimised use of saw blades.
- Integrated battery fuel gauge.
- Durable metal rafter hang hook for work space management and safety.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- **Supplied in case (HD Box) with battery and charger.**

### FEATURES

|                          |           |
|--------------------------|-----------|
| Symbol                   | M18FSZ-0X |
| Długość skoku            | 32.00     |
| Ilość akumulatorów       | brak      |
| Ilość suwów              | 0-3000    |
| Zasilanie                | battery   |
| Napięcie akumulatora [V] | 18        |