



SYMBOL: **4932352776** MANUFACTURER: **Milwaukee** EAN: **4002395374342**



## 4932352776 - Drill bit for concrete SDS-Max MX4, 4 cut, 25 x 800/920 mm

- Diameter: 25 mm
- Total length: 920 mm
- Working length: 800 mm
- Pack quantity: 1



469,58 zł **-10%**

**422,62 zł** (tax excl.)

(519,82 zł (tax incl.))



Product page

link > <https://im-narzedzia.pl/en/23365-4932352776-drill-bit-for-concrete-sds-max-mx4-4-cut-25-x-800920-...>



### DESCRIPTION

- Large carbide tip with patented rebar chamfers.
- Ensures lower vibration and optimised drilling performance when hitting reinforced steel equalling longer life time.
- Especially developed robust head geometry with optimum 4 x 90° symmetry of carbide tip. Reduces jamming up on hitting reinforcing steel.
- Centering point with 130° point angle. Easy spot drilling with pinpoint accuracy and ensures optimum guidance during drilling.
- Big, robust secondary cutter with dynamic, curved cutting edge. Supports the primary cutter for faster drilling.
- Shorter spiral windings. For faster transport of drilling dust from the head to the flute = Less wear and heat build up at the tip.
- Innovative, unique carbide tip. With more carbide on all diameters and extra carbide on  $\varnothing > 32$  mm.
- Wear mark on both sides of primary cutter. Guarantees diameter accuracy i.e. for anchor fittings.
- Life time indicator in warranty cases.
- Patented reinforced flute geometry. Lower vibrations for smoother drilling. Stronger flute means less breakages.
- Better transfer of hammer energy to the tip.
- Deep flute shoulders. High volume dust removal for optimum drilling speed less wear and heat build up.
- Low vibration drilling performance. Comfortable drilling ensures less stress for man and machine.
- Special surface treatment. Shot blasting provides a smooth surface and densifies the surface structure and makes the bit more wear resistant.
- PGM conformity. Guarantees precise holes for anchor fitting over the entire life time of the drill bit.

### FEATURES

Symbol	4932352776
L [mm]	920.00
D	25.00
Typ	4-ostrzowe
Ilość elementów	1
Długość robocza	800.00
Uchwyt	SDS-Max