PARTNER W DOBORZE ROZWIĄZAŃ TECHNICZNYCH DLA PRZEMYSŁU I MOTORYZACJI

ome > Cutting, drilling, abrasion > Drill bits > Concrete drill bits > SDS-MAX

SYMBOL: 4932352782 MANUFACTURER: Milwaukee EAN: 400	2395374403 * * * *
4932352782 - Drill bit for concrete	SDS-Max MX4, 4 cut, 28 x
1200/1320 mm	
• Diameter: 28 mm • Total length: 1320 mm • Working length: 1200 mm • Pack quantity: 1	
	Milwaukee
906,98 zł -10%	
816,28 zł (tax excl.)	
(1 004,02 zł (tax incl.))	Pay U[*] VISA MasterCard
Product page link > https://im-narzedzia.pl/en/23371-4932352782-drill-bit-for-c	oncrete-sds-max-mx4-4-cut-28-x-1200132

DESCRIPTION

- Large carbide tip with patented rebar chamfers.
- Large carbide tip with patentee repar charmers.
 Ensures lower vibration and optimised drilling performance when hitting reinforced steel equalling longer life time.
 Especially developed robust head geometry with optimum 4 x 90° symmetry of carbide tip. Reduces jamming up on hitting reinforcing steel.
 Centering point with 130° point angle. Easy spot drilling with pinpoint accuracy and ensures optimum guidance during drilling.
 Big, robust secondary cutter with dynamic, curved cutting edge. Supports the primary cutter for faster drilling.

- Shorter spiral windings. For faster transport of drilling dust from the head to the flute = Less wear and heat build up at the tip.
 Innovative, unique carbide tip. With more carbide on all diameters and extra carbide on Ø > 32 mm.
- Wear mark on both sides of primary cutter. Guarantees diameter accuracy i.e. for anchor fittings.
- Patented reinforced flute geometry. Lower vibrations for smoother drilling. Stronger flute means less breakages.
- Better transfer of hammer energy to the tip.
 Deep flute shoulders. High volume dust removal for optimum drilling speed less wear and heat build up.
- Low vibration drilling performance. Comfortable drilling ensures less stress for man and machine.
 Special surface treatment. Shot blasting provides a smooth surface and densifies the surface structure and makes the bit more wear resistant.
- · PGM conformity. Guarantees precise holes for anchor fitting over the entire life time of the drill bit.

FEATURES

Symbol	4932352782
L [mm]	1320.00
D	28.00
Тур	4-ostrzowe
Ilość elementów	1
Długość robocza	1200.00
Uchwyt	SDS-Max