

ne > Cutting, drilling, abrasion > Drill bits > Concrete drill bits > SDS-MAX



SYMBOL: **4932352786**

MANUFACTURER: Milwaukee EAN: 4002395374441

4932352786 - Drill bit for concrete SDS-Max MX4, 4 cut, 32 x 450/570 mm

- Diameter: 32 mm
- Total length: 570 mm
- Working length: 450 mm
- Pack quantity: 1



444,61 zl -10%

400,15 zł (tax excl.)

(492,18 zł (tax incl.))



link > https://im-narzedzia.pl/en/23375-4932352786-drill-bit-for-concrete-sds-max-mx4-4-cut-32-x-450570-...



DESCRIPTION

- · Large carbide tip with patented rebar chamfers
- Ensures lower vibration and optimised drilling performance when hitting reinforced steel equalling longer life time.
- Especially developed robust head geometry with optimum 4 x 90° symmetry of carbide tip. Reduces jamming up on hitting reinforcing steel.
- Centering point with 130° point angle. Easy spot drilling with pinpoint accuracy and ensures optimum guidance during drilling.
 Big, robust secondary cutter with dynamic, curved cutting edge. Supports the primary cutter for faster drilling.
- Shorter spiral windings. For faster transport of drilling dust from the head to the flute = Less wear and heat build up at the tip.
 Innovative, unique carbide tip. With more carbide on all diameters and extra carbide on Ø > 32 mm.
- · Wear mark on both sides of primary cutter. Guarantees diameter accuracy i.e. for anchor fittings.
- Patented reinforced flute geometry. Lower vibrations for smoother drilling. Stronger flute means less breakages.
- Better transfer of hammer energy to the tip.
 Deep flute shoulders. High volume dust removal for optimum drilling speed less wear and heat build up.
- Low vibration drilling performance. Comfortable drilling ensures less stress for man and machine.
 Special surface treatment. Shot blasting provides a smooth surface and densifies the surface structure and makes the bit more wear resistant.
- PGM conformity. Guarantees precise holes for anchor fitting over the entire life time of the drill bit.

FEATURES

Symbol	4932352786
L [mm]	570.00
D	32.00
Тур	4-ostrzowe
Ilość elementów	1
Długość robocza	450.00
Uchwyt	SDS-Max