




SYMBOL: **4933478892** MANUFACTURER: **Milwaukee** EAN: **4058546361747**



M18 BLHX-502X - 4-mode 26 mm SDS-Plus hammer 18 V, 5.0 Ah, in case, with 2 batteries and charger

- Voltage: 18 V
- Blow energy: 2.3 J
- Max. percussion rate: 0-5100 bpm
- No load speed: 0-1400 rpm
- Max. drilling wood/steel/concrete: 26/13/26 mm
- Vibration drilling: 8.9 m/s²
- Vibration chiseling: 9.5 m/s²
- Tool reception: SDS-Plus + Reduced shank 13 mm
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 3.5 kg

 **WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~2 669,00 zł~~ **-10%**

2 402,10 zł (tax excl.)

(2 954,58 zł (tax incl.))

PayU  

Product page

link > <https://im-narzedzia.pl/en/25570-m18-blhx-502x-4-mode-26-mm-sds-plus-hammer-18-v-50-ah-in-case-wi...>

DESCRIPTION

- Powerful hammer mechanism and the brushless motor design delivers 2.3 J of impact energy.
- Compact, ergonomic design for increased end user comfort.
- FIXTEC™ system for keyless chuck changing between SDS-Plus and 13 mm metal chuck.
- All metal gear case - optimum seating of the gears for enhanced tool life.
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility.
- Anti-vibration side handle for lower vibration exposure.
- Compatible with M18 CDEX dust extractor.
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- **Supplied in case (HD Box) with 2 batteries and charger.**

FEATURES

Symbol	M18BLHX-502X
Waga [kg]	3.50
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-5100
Energia uderu	2.30
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	26.00
Średnica wiercenia w drewnie	26.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1400

