

ne > Power tools > Batteries and chargers > Batteries



DESCRIPTION

Charge time:

- Fast charger M12-18 FC: 40 min
- Standard charger C12 C/ M12-18C/ M12 C4/ M12-18 AC: 55 min / M12-18 SC: 40 min / M12 TC: 200 min
 The new M12[™] 2.5 Ah HIGH OUTPUT[™] battery pack provides up to 25% more the power vs M12 B2 REDLITHIUM[™] battery pack
- Runs up to 25% cooler then other M12 methods up to 25% inter the other M12 to 25% cooler then other M12 methods.
 Sophisticated electronics: REDLINK[™] intelligence.
- Overload protection prevents user from damaging their cordless power tool investment in abusive situations
 Temperature management system keeps battery in ideal temperature range to provide maximum life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Discharge protection prevents cell damage from over-discharge.
- *Compared with other Lithium -Ion technologies and / or with previous MILWAUKEE® battery technology. Results dependent on voltage, tool and application.
- Integrated welded frame battery construction with shock responsive separators preventing pack failure from excessive vibrations or drops.
 Can be used in extreme temperatures down to -20 °C without compromising on run time and battery life.

· Improved housing is resistant to oils, solvents and greases.

FEATURES

Symbol	M12HB2.5
Napięcie akumulatora [V]	12
Pojemność akumulatora [Ah]	2.5
System	M12™
Typ akumulatora	Li-lon