



SYMBOL: **4933479872** MANUFACTURER: **Milwaukee** EAN: **4058546376666**



M12 FDD2-0 - Sub compact drill driver 12 V, FUEL™, without equipment, 4933479872

- Voltage: 12 V
- Max. torque: 45 Nm
- Max. drilling wood/steel: 35/13 mm
- No load speed gear 1/gear 2: 0-450/0-1550 rpm
- Chuck capacity: 13 mm
- Speed settings: 2
- Wood screws to: 8 mm
- Battery type: Li-ion
- Weight with battery pack (M12 B6): 1.4 kg



799,00 zł **-10%**

719,10 zł (tax excl.)

(884,49 zł (tax incl.))



Product page

link > <https://im-narzedzia.pl/en/26728-m12-fdd2-0-sub-compact-drill-driver-12-v-fuel-without-equipment...>

DESCRIPTION

- Vibration drilling into metal: 1.92 m/s²
- Vibration screw driving: 0.86 m/s²
- Sound pressure level (LPA): 74.8 dB(A)
- Sound power level (LWA): 85.8 dB(A)
- Extremely compact design of 151 mm length for access into tight spaces.
- 45 Nm of torque - superior power to size ratio.
- 13 mm heavy duty metal chuck for quick bit changes and bit retention.
- Mechanical clutch with 13 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer.
- On board fuel gauge, metal belt clip and LED light.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.
- Supplied without battery and charger.

FEATURES

| | |
|--------------------------------|--------------|
| Symbol | M12FDD2-0 |
| Typ | bezarowa |
| Nm max | 45.00 |
| Ilość akumulatorów | brak |
| Ilość biegów | 2 |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 12 |
| Średnica uchwytu wiertarskiego | 13.00 |
| Średnica wiercenia w drewnie | 35.00 |
| Średnica wiercenia w metalu | 13.00 |
| Obroty [obr/min] | 0-450/0-1550 |