



SYMBOL: 4933480593

MANUFACTURER: Milwaukee

EAN: 4058546408787

M12 FPP2D2-422X - POWERPACK M12™, M12 FPD2, M12 BPRT, 2.0 and 4.0 Ah + charger, in case, 4933480593

- · Set includes:
- M12 FPD2 percussion drill
- M12 BPRT subcompact rivet tool
- M12 B2, M12 B4 2 batteries 2.0 and 4.0 Ah
- C12 C charger
- · Supplied in case (HD Box).

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



2 529,00 zł -10%

2 276,10 zł (tax excl.)

(2 799,60 zł (tax incl.))



Pavu VISA MasterCard



link > https://im-narzedzia.pl/en/26800-m12-fpp2d2-422x-powerpack-m12-fpd2-m12-bprt-20-and-40-ah-cha...

DESCRIPTION

M12 FPD2

- · Voltage: 12 V Max. percussion rate: 0-22500 bpm
- · Max. torque: 45 Nm
- Max. drilling wood/steel/masonry: 35/13/13 mm
- No load speed gear 1/gear 2: 0-450/0-1550 rpm
 Chuck capacity: 13 mm
- · Speed settings: 2
- · Wood screws to: 8 mm
- Weight with battery pack (M12 B6): 1.4 kg
- Vibration drilling into concrete/metal: 15.73/1.92 m/s²
- Vibration screw driving: 0.86 m/s²
 Sound pressure level (LPA): 89.3 dB(A)
- · Sound power level (LWA): 100 dB(A)
- Extremely compact design of 152 mm length for access into tight spaces.
- 45 Nm of torque superior power to size ratio.
- Mechanical clutch with 13 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer
- On board fuel gauge, metal belt clip and LED light.
 The DNA of our FUEL™ platform redefines the balance of cordless technologies
- MILWAUKEE®'s POWERSTATE" brushless motor, REDLITHIUM* battery pack and REDLINK PLUS* electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

M12 BPRT

- Voltage: 12 V
 Stroke length: 20.32 mm
- Rivet diameter range: 2.4 4.8 mm Max. pulling force: 9000 N
- Battery type: Li-ionDimensions: 273 x 66 x 8 x 230 mm
- Weight with battery pack: 2.1 kg
- Sound power and pressure level: 64.1 / 53.1 dB(A)
- Up to 325 x 4.8 mm stainless steel rivets on a single charge with a 2.0 Ah battery pack.
- \bullet Suitable for all aluminium, steel, stainless steel and copper rivets up to 4.8 mm. \bullet Rivets in one stroke with a 20.32 mm stroke length.
- · Retention nose pieces hold rivets in any orientation.
- Tool-free access to easily clean jaws. On-board nose piece storage and removal tool for user convenience.
- On board fuel gauge and LED light for added user convenience and illumination in low lit working conditions.
- Ergonomic design with 273 mm H x 66.8 mm W x 165 mm in length without mandrel collector
- egrated belt hook and lanyard tie off point.
- REDLITHIUM*-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

Supplied in case (HD Box) with 2 batteries and charger.

FEATURES







Symbol	M12FPP2D2-422X
Opis	wiertarko-wkrętarka udarowa, nitownica, 2 akumulatory, ładowarka
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Pojemność akumulatora [Ah]	2.0, 4.0