



SYMBOL: **4932492932** MANUFACTURER: **Milwaukee** EAN: **4058546478032**



## M12 NRG01-643 - Set of 3 batteries M12™, Li-ion 12 V, 4.0 Ah, 2 x 6.0 Ah + charger, 4932492932

- System M12™
- Battery type: Li-ion
- Battery pack capacity: 4.0 and 6.0 Ah
- Charger supplied: 80/130 min
- Set contains:
  - 1 battery M12™ 4.0 Ah: M12 B4
  - 2 batteries M12™ 6.0 Ah: M12 B6
  - charger M12™: C12 C

**WARRANTY: MANUFACTURER WARRANTY**



~~1 229,00 zł~~ **-10%**

**1 106,10 zł** (tax excl.)

(1 360,50 zł (tax incl.))

PayU

Product page

link > <https://im-narzedzia.pl/en/26995-m12-nrg01-643-set-of-3-batteries-m12-li-ion-12-v-40-ah-2-x-60-ah...>

### DESCRIPTION

#### C12 C

- Temperature protection electronics optimises the charger rate in extreme temperatures to extend battery life.
- Encapsulated circuit board protects the electronics from dust, moisture and impact.
- Progressive charge indication: battery LED's light up incrementally to give feedback on current charge level of battery pack.

#### M12 B4

- Charge time:
  - Fast charger M12-18 FC: 40 min
  - Standard charger C12 C/ M12-18C/ M12 C4: 80 min / M12-18 AC: 115 min / M12 TC: 347 min
- Delivers up to 2x more run time, up to 20% more power and up to 2x more battery life compared with other Lithium-ion technologies and/or with previous MILWAUKEE® battery technology (Results depend on tool and application).
- REDLITHIUM™-ION protection with REDLINK™ digital overload protection to prevent users from damaging their cordless power tool investment in abusive situations.
- Individual cell monitoring ensures optimal charge and discharge for maximum life.
- Integrated welded frame battery construction with shock responsive separators preventing pack failure from excessive vibrations or drops.
- Can be used in extreme temperatures down to -20 °C without compromising on runtime and battery life.
- Discharge protection prevents cell damage from over-discharge.

#### M12 B6

- Charge time:
  - Fast charger M12-18 FC: 60 min
  - Standard charger C12 C/ M12-18C/ M12 C4: 130 min / M12-18 AC: 165 min / M12 TC: 525 min
- Delivers up to 3x more run time, up to 20% more power and up to 2x more battery life compared with other Lithium-ion technologies and/or with previous Milwaukee® battery technology (Results depend on tool and application).
- REDLITHIUM™-ION™ protection with Milwaukee® REDLINK™ digital overload protection to prevent users from damaging their cordless power tool investment in abusive situations.
- Individual cell monitoring ensures optimal charge and discharge for maximum life.
- Integrated welded frame battery construction with shock responsive separators preventing pack failure from excessive vibrations or drops.
- Can be used in extreme temperatures down to -20 °C without compromising on runtime and battery life.
- Discharge protection prevents cell damage from over-discharge.

### FEATURES

Symbol	M12NRG01-643
Napięcie akumulatora [V]	12
Pojemność akumulatora [Ah]	4.0, 6.0
System	M12™
Typ akumulatora	Li-Ion