



SYMBOL: **4933492480** MANUFACTURER: **Milwaukee** EAN: **4058546418472**



## M18 BLHACD26-402X - Brushless 26 mm SDS-Plus D-Handle hammer 18 V, 4.0 Ah, in case, with 2 batteries and charger, 4933492480

- Voltage: 18 V
- Blow energy: 2.6 J
- Max. percussion rate: 0-4600 bpm
- No load speed: 0-1270 rpm
- Max. drilling concrete/wood/steel: 26/28/13 mm
- Tool reception: SDS-Plus
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 4.0 Ah
- Weight with battery pack (M18 B4): 3.1 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~2 199,00 zł~~ **-10%**

**1 979,10 zł** (tax excl.)

(2 434,29 zł (tax incl.))

PayU

Product page

link > <https://im-narzedzia.pl/en/30830-m18-blhacd26-402x-brushless-26-mm-sds-plus-d-handle-hammer-18-v-...>

### DESCRIPTION

- Vibration drilling: 13.9 m/s<sup>2</sup>
- Vibration chiseling: 13.2 m/s<sup>2</sup>
- Sound pressure level (LPA): 93.5 dB(A)
- Sound power level (LWA): 104.5 dB(A)

- D-handle with lightweight and ergonomic design for increased end user comfort.
- Powerful hammer mechanism and the brushless motor design delivers 2.6 J of impact energy.
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility.
- Anti-vibration system (AVS) for decreased user fatigue and lower vibration exposure.
- All metal gear case, optimum seating of the gears for enhanced service life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- **Supplied in case (HD Box) with 2 batteries and charger.**

### FEATURES

Symbol	M18BLHACD26-402X
Waga [kg]	3.10
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-4600
Energia uderu	2.60
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	26.00
Średnica wiercenia w drewnie	28.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1270