
















MANUFACTURER: Milwaukee EAN: 4058546373832



M18 FTHCHS35-802 - Top handle chainsaw with 35 cm bar, 18 V, 8.0 Ah, FUEL™, with 2 batteries and charger, 4933479589

- · Voltage: 18 V
- · Chain bar length: 35 cm
- U sable cutting length: 34.3 cm
- Drive links: 59
- · Oil tank capacity: 0.2 l
- · Chain speed: 15 m/s
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 8.0 Ah
- Weigth with battery pack (M18 HB8): 4.7 kg





4 294,00 zł -10%

3 864,60 zł (tax excl.)

(4 753,46 zł (tax incl.))



PayUi VISA MasterCard

link > https://im-narzedzia.pl/en/30984-m18-fthchs35-802-top-handle-chainsaw-with-35-cm-bar-18-v-80-ah-f...

## DESCRIPTION

- · Outstanding speed of cut in hardwood vs certain petrol or higher voltage top handle chainsaws
- High torque to complete cuts in demanding materials and maintains speed under heavy loads without bogging down.
  FUEL\*\* technology to reach full throttle in under 1 second.
- Up to 150 cuts in 10 x 10 cm cedar on a full M18™ HIGH OUTPUT™ 8.0 Ah battery charge for outstanding productivity.
- · Top handle design and optimised balance perfectly suited for arboricultural work
- Variable speed trigger allows for full control over the power curve.
- Ergonomic angled bail handle for convenient handling in multiple positions
- · All metal bucking spikes allow the user increased leverage when cutting.
- No-spill oil reservoir with easy to access tank and clear viewing window
- Supplied with 76cc of oil, chain tool and bar cover.
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- · Standard Equipment: 76cc of oil, chain tool, bar cover
- Supplied with 2 batteries and charger.

## FEATURES

LATOREO	
Symbol	M18FTHCHS35-802
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Długość prowadnicy/łańcucha [mm]	350.00