




SYMBOL: 4933493304

MANUFACTURER: Milwaukee EAN: 4058546481759

M18 FR12-0X - Router 12 mm, 18 V, FUEL™, in case, without equipment, 4933493304

- · Voltage: 18 V
- · Collect capacity: 12.7 mm
- Plunge capacity: 60 mm
- Speed settings: 6
- No load speed: 12000-25000 rpm
- · Battery type: Li-ion
- No. of batteries supplied: 0
- Weigth with battery pack (M18 HB5.5): 4 kg





2 299,00 zł -10%

2 069,10 zł (tax excl.)

(2 544,99 zł (tax incl.))



Pay**U**i VISA MasterCard













link > https://im-narzedzia.pl/en/30990-m18-fr12-0x-router-12-mm-18-v-fuel-in-case-without-equipment-493...

DESCRIPTION

- POWERSTATE™ brushless motor in combination with the HIGH OUTPUT™ 5.5 Ah battery pack supplies constant power for faster
- cuts and reduced heat in high demand applications with the equivalent amount of power as a corded unit. $\cdot \text{Variable speed from } 12,000 \text{ RPM to } 25,000 \text{ RPM for clean and accurate cutting in a wide range of material.}$
- Fast and accurate micro depth adjustments with no slop, secure macro adjustments, and clear line of sight to the bit when routing the workpiece.
- · Unobstructed line of sight to the bit to gauge cut quality, feed rate, and material removed per pass.
- $\bullet \textit{Easily controlled with one hand, comfortable to use at extended duration's, and well-balanced across the base plate onto the work surface.} \\$
- · Guide rail compatible, gives the user a secure and efficient method to attach their router bases to a guide rail system to cut straight lines on any work surface
- Collet diameters are 12 mm, 1/2", 8 mm, 1/4".
- · Duel LED work light to illuminate the work piece.
- DEK 26 quick dust extraction connector makes the router compatible with any MILWAUKEE® vac.
- The DNA of our FUEL" platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE" brushless motor, REDLITHIUM" battery pack and REDLINK PLUS" electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
 Standard Equipment: 1/4", 8 mm, 12 mm, 1/2" collets, side fence, sub base, wrench, dust extraction pipe.
- Supplied in case (HD Box) without battery and charger.

FEATURES

-EATURES	
Symbol	M18FR12-0X
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	12000-25000