



SYMBOL: **4933492783** MANUFACTURER: **Milwaukee** EAN: **4058546476540**



**M18 FHIW2F12-502X - High torque impact wrench 1/2", 1491 Nm, 18V, 5.0Ah, FUEL™, in case with 2 batteries and charger, 4933492783**

- Voltage: 18 V
- Max. torque: 881/ 1220/ 1491/ 68 Nm
- Nut-busting torque: 2034 Nm
- Impact rate: 0-1300/ 0-2200/ 0-2400/ 0-2400 ipm
- No load speed: 0-700/ 0-1300/ 0-2000/ 0-2000 rpm
- Tool reception: 1/2" square
- Max. bolt diameter: M36
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 5.0 Ah
- Weight with battery pack (M18 B5): 3.4 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~3 039,00 zł~~ **-10%**

**2 735,10 zł** (tax excl.)

(3 364,17 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://im-narzedzia.pl/en/32047-m18-fhiw2f12-502x-high-torque-impact-wrench-12-1491-nm-18v-50ah-...>

## DESCRIPTION

- Great power density: the M18 FUEL™ high torque impact wrench delivers 1491 Nm fastening torque and 2034 Nm of nut-busting torque in a compact size of 193 mm, which gives more access in tight spaces.
- 2000 RPMs of no load speed to perform your task 35% faster than with the previous gen.
- Our battery isolation system provides a secure battery connection and controls vibration transmitted to the pack.
- Robust gearcase for more durability.
- Tri-LEDs deliver high-definition lighting to increase workspace visibility.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 4 bolt removal, provides maximum nut-busting torque then shifts to 750 rpm for outstanding control when removing fasteners.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- **Supplied in case (HD Box) with 2 batteries and charger.**

## FEATURES

Symbol	M18FHIW2F12-502X
Wyjście	1/2"
Nm max	1491
Częstość uderu [ud/min]	1300/2200/2400/2400
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	700/1300/2000/2000