



SYMBOL: **4933492820** MANUFACTURER: **Milwaukee** EAN: **4058546476915**



M18 BLPDRC-0 - Compact brushless percussion drill 60.5 Nm, 18 V, without equipment, 4933492820

- Voltage: 18 V
- Max. torque: 60.5 Nm
- No load speed gear 1/2: 0-550/0-1700 rpm
- Max. drilling wood/steel/masonry: 52/16/13 mm
- Max. percussion rate: 0-25500 bpm
- Chuck capacity: 13 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight: 1 kg
- Weight with battery pack (M18 B5): 1.5 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~709,00 zł~~ **-20%**

567,20 zł (tax excl.)

(697,66 zł (tax incl.))



Product page

link > <https://im-narzedzia.pl/en/32051-m18-blpdrc-0-compact-brushless-percussion-drill-605-nm-18-v-with...>

DESCRIPTION

- Vibration screw driving: 1.44 m/s²
- Vibration drilling into concrete: 8.31 m/s²
- Vibration drilling into metal: 1.64 m/s²
- Sound pressure level (LPA): 90.66 dB(A)
- Sound power level (LWA): 98.66 dB(A)
- Compact brushless percussion drill measuring 145 mm in length for access into tight spaces.
- Advanced 13 mm heavy duty metal chuck for quick bit changes and superior bit retention.
- 60.5 Nm of torque - best power to size ratio.
- All metal reversible belt clip to hang your tool quickly and easily.
- On board fuel gauge and LED light.
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Optimised speed for faster drilling & fastening (0 - 550/ 0 - 1700 rpm).
- **Supplied without battery and charger.**

FEATURES

| | |
|--------------------------------|--------------|
| Symbol | M18BLPDRC-0 |
| Typ | udarowa |
| Nm max | 60.50 |
| Częstość uderu [ud/min] | 0-25500 |
| Ilość akumulatorów | brak |
| Ilość biegów | 2 |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 18 |
| Średnica uchwytu wiertarskiego | 13.00 |
| Średnica wiercenia w drewnie | 52.00 |
| Średnica wiercenia w metalu | 13.00 |
| Średnica wiercenia w murze | 16.00 |
| Obroty [obr/min] | 0-550/0-1700 |