



SYMBOL: **4933498060** MANUFACTURER: **Milwaukee** EAN: **4058546512200**



M18 FPD3-0 - Percussion drill 158 Nm, 18 V, FUEL™, without equipment, 4933498060

- Voltage: 18 V
- Max. torque: 158 Nm
- No load speed gear 1/2: 0-500/0-2100 rpm
- Max. drilling wood/steel/masonry: 89/16/16 mm
- Max. percussion rate: 0-33000 bpm
- Chuck capacity: 13 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack (M18 B5): 2.2 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~1 199,00 zł~~ **-10%**

1 079,10 zł (tax excl.)

(1 327,29 zł (tax incl.))

PayU

Product page

link > <https://im-narzedzia.pl/en/33306-m18-fpd3-0-percussion-drill-158-nm-18-v-fuel-without-equipment-4...>

DESCRIPTION

- Vibration screw driving: 1.48 m/s²
- Vibration drilling into concrete: 11.3 m/s²
- Vibration drilling into metal: 1.85 m/s²
- Sound pressure level (LPA): 95.78 dB(A)
- Sound power level (LWA): 106.78 dB(A)
- Higher power efficiency under load with outstanding torque of 158 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- AUTOSTOP™ control mode offers enhanced safety for the operator by preventing over-rotation in a bind-up.
- 13 mm metal chuck for quick bit changes and bit retention.
- Fastest drilling and driving applications under load.
- Brighter LED workspace illumination.
- Fuel gauge displays remaining charge.
- All metal reversible belt clip to hang your tool quickly and easily.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Supplied without battery and charger.

FEATURES

| | |
|--------------------------------|--------------|
| Symbol | M18FPD3-0 |
| Typ | ударова |
| Nm max | 158.00 |
| Częstość udaru [ud/min] | 0-33000 |
| Ilość akumulatorów | brak |
| Ilość biegów | 2 |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 18 |
| Średnica uchwytu wiertarskiego | 13.00 |
| Średnica wiercenia w drewnie | 89.00 |
| Średnica wiercenia w metalu | 16.00 |
| Średnica wiercenia w murze | 16.00 |
| Obroty [obr/min] | 0-500/0-2100 |